

**PVC 150# Cover One Side Black Crescent Top**

Application

The crescent top profile is very popular for use in general purpose incline applications. The durable all polyester interwoven carcass provides low stretch, excellent fastener retention and good tear resistance. The economical PVC cover compound has superior mineral oil resistance as well as excellent wear characteristics.

Technical Data

	Imperial
Working Tension	150 PIW
Number of Plies	1
Fabric Type	Spun Poly
Top Surface	Crescent Top
Bottom Surface	Brushed
Overall Gauge (Approximate)	0.255 in.
Weight (Approximate)	1.22 lbs/sq.ft.
Bottom Coefficient of Friction	0.25 (approx.)
Minimum Recommended Pulley Diameter	2.5 in.
Elongation at Rated Tension	< 2%
Working Temperature	20 to 180 F

\* Low temperature based on intermittent conditions.

Splicing Methods

FOF	Finger	Bias Stepped	Skived Bias	Clipper*	Alligator*	Staple*
No	Yes	No	Yes	2 or U2	20	125

\* Fastener manufacturer should be consulted to review belt and application information.

Compliance (Government Regulations)

FDA/USDA	OSHA	MSHA	CSA	FRAS	NCB
	< 300 Megohms	CFR 18.65	M422-87	1334.12	158:1989
No	No	No	No	No	No