

PVC 120# Cover One Side Black Mini-Rough Top

Application

This quiet running, rugged belt is excellent in postal facilities, airports, automotive plants and package handling systems. The mini-rough top impression provides long lasting grip and appearance for incline applications. Whisper weave brushed bottom offers quiet running service in slider bed applications and monofilament in the top fabric ply provides transverse rigidity. This belt also offers superior tracking performance, edge wear resistance and flexibility over small pulleys.

Technical Data

	Imperial
Working Tension	120 PIW
Number of Plies	2
Fabric Type	Whisper Spun & Mono
Top Surface	Mini-Rough Top
Bottom Surface	Friction
Overall Gauge (Approximate)	0.140 in.
Weight (Approximate)	1.00 lbs/sq.ft.
Bottom Coefficient of Friction	0.35 (approx.)
Minimum Recommended Pulley Diameter	2.0 in.
Elongation at Rated Tension	< 2%
Working Temperature	20 to 180 F

Splicing Methods

FOF	Finger	Bias Stepped	Skived Bias	Clipper*	Alligator*	Staple*
Yes	Yes	Yes	Yes	2 or U2	20	125

* Fastener manufacturer should be consulted to review belt and application information.

Compliance (Government Regulations)

FDA/USDA	OSHA	MSHA	CSA	FRAS	ISO
	< 300 Megohms	2G Flame	M422-87	1334.12	340
No	No	Yes	Yes	No	Yes