

**2-Ply PVC 150# Cover Both Sides Black**

Application

This plied belt has been specially designed for recycling, agricultural and industrial applications for conveying of oily products, grains, feeds, fertilizers, agriculture and produce. The moderately oil resistant PVC compound provides low temperature capabilities and resistance to slider abrasion. This belt also offers superior tracking performance.

Technical Data

	Imperial
Working Tension	150 PIW
Number of Plies	2
Fabric Type	Spun Poly
Top Surface	Satin
Bottom Surface	Satin
Overall Gauge (Approximate)	0.160 in.
Weight (Approximate)	1.05 lbs/sq.ft.
Bottom Coefficient of Friction	0.50 (approx.)
Minimum Recommended Pulley Diameter	2.5 in.
Elongation at Rated Tension	< 2%
Working Temperature	-20 to 180 F

\* Low temperature based on intermittent conditions.

Splicing Methods

FOF	Finger	Bias Stepped	Skived Bias	Clipper*	Alligator*	Staple*
Yes	Yes	Yes	Yes	2 or U2	15	125

\* Fastener manufacturer should be consulted to review belt and application information.

Compliance (Government Regulations)

FDA/USDA	OSHA	MSHA	CSA	FRAS	NCB
	< 300 Megohms	CFR 18.65	M422-87	1334.12	158:1989
No	No	No	No	No	No