all-state INDUSTRIES, inc.
belting • rubber • plastics • urethane

PVC 200# Cover One Side Black Crescent Top

Application

The crescent top profile is very popular for use in general purpose incline applications. The durable all polyester interwoven carcass provides low stretch, excellent fastener retention and good tear resistance. The economical PVC cover compound has superior mineral oil resistance as well as excellent wear characteristics.

Technical Data

	Imperial
Working Tension	**200 PIW**
Number of Plies	**1**
Fabric Type	**Spun Poly**
Top Surface	**Crescent Top**
Bottom Surface	**Brushed**
Overall Gauge (Approximate)	**0.315 in.**
Weight (Approximate)	**1.45 lbs/sq.ft.**
Bottom Coefficient of Friction	**0.25 (approx.)**
Minimum Recommended Pulley Diameter	**4.0 in.**
Elongation at Rated Tension	**< 2%**
Working Temperature	**20 to 180 F**

** Low temperature based on intermittent conditions.*

Splicing Methods

FOF	Finger	Bias Stepped	Skived Bias	Clipper*	Alligator*	Staple*
No	Yes	No	Yes	4 or UX1	27	187

** Fastener manufacturer should be consulted to review belt and application information.*

Compliance (Government Regulations)

FDA/USDA	OSHA	MSHA	CSA	FRAS	NCB
	< 300 Megohms	CFR 18.65	M422-87	1334.12	158:1989
No	No	No	No	No	No